


10.15 - RACCORDI SUPER RAPIDI IN ACCIAIO INOX 316

Pressione 18 bar; Temperatura Aria: -20 + 110° C; Temperatura Acqua: -0 + 110° C

Infratubo dritto liscio


Cod.: RVA 658 ...²⁾



Ø ²⁾ Tubo (mm)
4
6
8
10
12

Angolo 90° filetto maschio gas conico fisso


Cod.: RVA 650 ...¹⁾ ...²⁾



Ø ²⁾ Tubo (mm)	Øg ¹⁾ fil.maschio (inch)
4	1/8"
6	1/8"
6	1/4"
8	1/4"
10	1/4"
12	1/4"

Dritto con filetto maschio gas conico


Cod.: RVA 651 ...¹⁾ ...²⁾



Ø ²⁾ Tubo (mm)	Øg ¹⁾ fil.maschio (inch)
4	1/8"
6	1/8"
6	1/4"
8	1/8"
8	1/4"
10	1/4"
10	3/8"
12	1/4"
12	3/8"

"T" infratubo

Cod.: RVA 654 ...²⁾



Ø ²⁾ Tubo (mm)
4
6
8
10
12

Angolo a 90° infratubo

Cod.: RVA 655 ...²⁾



Ø ²⁾ Tubo (mm)
4
6
8
10
12

"T" con filetto maschio gas con. centrale



Ø ¹⁾ Tubo (mm)	Øg ²⁾ fil.maschio (inch)
4	1/8"
6	1/8"
6	1/4"
8	1/4"
10	1/4"
12	1/4"

Dritto con filetto maschio cilindrico con OR


Cod.: RVA 651C ...¹⁾ ...²⁾



Ø ²⁾ Tubo (mm)	Øg ¹⁾ fil.maschio (inch)
4	1/8"
6	1/8"
6	1/4"
8	1/8"
8	1/4"
10	1/4"
10	3/8"
12	1/4"
12	3/8"
12	1/2"

Adattatore cilindrico con OR


Cod.: RVA 681 ...¹⁾ ...²⁾



Ø ²⁾ Tubo (mm)	Øg ¹⁾ fil.maschio (inch)
4	1/8"
6	1/8"
8	1/4"
10	1/4"
12	3/8"
12	1/2"
12	1/2"

RIDUZIONE

Cod.: RVA 680 ...¹⁾ ...²⁾



Ø ²⁾ Tubo (mm)	Ø ¹⁾ tubo
6	4
8	4
8	6
10	6
10	8
12	6
12	8
12	10